

WHEELS

Product group	Wheels
Item number	59913216
Valid wheel size	420 / 55 - 17
Brand	BKT
Tread pattern	AW 726
Valid rim size	13.00 x 17
Rim connection	6/161/205
Bolt hole design	E2
Offset (mm)	-40
Rim colour	Silver
Load capacity complete wheel [kg]	2060
Speed complete wheel [km/h]	40
Nettogewicht [kg] (gültig)	65,01
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15711866
LI / SI / PR	121 A8 / 133 A8
Load capacity 1 [kg]	1450
Speed 1 [km/h].	40
Load capacity 2 [kg]	2060
Speed 2 [km/h].	40
Maximum air pressure [bar].	2,00
TL/TT	TL

Tyre colour	Black
E-Ready	No
Antistatic	No
ECE regulation number	ECE 106
Section width (mm)	415
Stat. radius (SLR) [mm]	392
Rolling circumference [mm].	2584
Tread depth (mm)	13,5
Assembly Item no. Rim	• 32010310
Load capacity of rim 1 [kg]	3300
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Type of drive	Angetriebene & gezogene Achse
Number of bolt holes	6
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Ventilation holes	No
Single / multi-part	einteilig
Hump	kein Hump
Cavity Sealed	No

Verschweißung beidseitig	No
Assembly Item no. Valve	• 47200570
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Rubber valve
Valve designation ETRTO	V2.03.3
Valve length [mm]	43.0
Valve angle [°]	gerade