

WHEELS

Product group	Wheels
Item number	59915871
Valid wheel size	800 / 45 R 30.5
Brand	Alliance
Tread pattern	885
Valid rim size	AG 28.00 x 30.5 H2
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	-50
Rim colour	Silver
Load capacity complete wheel [kg]	7100
Speed complete wheel [km/h]	65
Nettogewicht [kg] (gültig)	321,71
RDA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15215808
LI / SI / PR	176 D
Load capacity 1 [kg]	7100
Speed 1 [km/h].	65
Maximum air pressure [bar].	4,00
TL/TT	TL
Tyre colour	Black
E-Ready	No

Carcass properties	Steel Belted
Antistatic	No
Direction	Left
ECE regulation number	ECE 106
Section width (mm)	790
Stat. radius (SLR) [mm]	665.00
Speed Radius Index (SRI)	725
Rolling circumference [mm].	4533
Tread depth (mm)	26,8
Number of lugs	24x2
Assembly Item no. Rim	• 10001522
Load capacity of rim 1 [kg]	12200
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	9000
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Type of drive	Towed axle
Number of bolt holes	10
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Bolt hole design EUWA	B22 ES 36
Countersinking	Sphere
Spherical countersink [mm].	R18
Rim centering	BC
Rim material	steel
RAL	RAL9006

Valve seat	External Valve
Ventilation holes	No
Single / multi-part	einteilig
Hump	H2
Valve protection	VSH
Cavity Sealed	No
Knurling	without knurling
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201039
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade