

## WHEELS

Product group	Wheels
Item number	59916065
Valid wheel size	500 / 85 R 24
Brand	BKT
Tread pattern	RM 500
Valid rim size	DW 15 L x 24
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	-50
Rim colour	Silver
Load capacity complete wheel [kg]	8500
Speed complete wheel [km/h]	40
Nettogewicht [kg] (gültig)	242,22
RDA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 15727835
LI / SI / PR	170 A8 / 182 A8
Load capacity 1 [kg]	6000
Speed 1 [km/h].	40
Load capacity 2 [kg]	8500
Speed 2 [km/h].	40
Maximum air pressure [bar].	4,00
TL/TT	TL

Tyre colour	Black
E-Ready	No
Carcass properties	Steel Belted
Antistatic	No
ECE regulation number	ECE 106
Section width (mm)	520
Stat. radius (SLR) [mm]	622
Speed Radius Index (SRI)	700
Rolling circumference [mm].	4382
Tread depth (mm)	38,0
Number of lugs	20x2
Assembly Item no. Rim	• 33060885
Load capacity of rim 1 [kg]	5750
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	4850
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Number of bolt holes	10
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Bolt hole design EUWA	B22 DS 36
Countersinking	Sphere
Spherical countersink [mm].	R18
Rim centering	BC
Rim material	steel
RAL	RAL9006

Valve seat	External Valve
Ventilation holes	No
Single / multi-part	einteilig
Hump	kein Hump
Valve protection	VSH
Cavity Sealed	No
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201038
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade