

WHEELS

Product group	Wheels
Item number	59916286
Valid wheel size	380 / 90 R 50
Brand	Alliance
Tread pattern	350
Valid rim size	W 12 x 50
Rim colour	Red
Nettogewicht [kg] (gültig)	316,49
RDA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No





Technical Informations

Assembly Item no. Tyres •	15226676
LI / SI / PR	161 A8 / 158 D
Load capacity 1 [kg]	4625
Speed 1 [km/h].	40
Load capacity 2 [kg]	4250
Speed 2 [km/h].	65
Maximum air pressure [bar].	3,60
TL/TT	TL
Tyre colour	Black
E-Ready	No
Antistatic	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



ECE regulation number	ECE 106
Section width (mm)	384
Stat. radius (SLR) [mm]	916
Rolling circumference [mm].	5939
Tyre capacity 75% [ltr.]	325.5
Assembly Item no. Rim •	39123069
Load capacity of rim 1 [kg]	4659
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	4261
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Type of drive	Angetriebene & gezogene Achse
Rim centering	BC
Rim material	steel
RAL	RAL3000
Valve seat	External Valve
Ventilation holes	No
Single / multi-part	einteilig
Hump	kein Hump
Surface treatment	SB
Cavity Sealed	No
Verschweißung beidseitig	No
Assembly Item no. Valve •	47201038
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Metal valve

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.





Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade