

WHEELS

Product group	Wheels
Item number	59917476
Valid wheel size	710 / 40 R 22.5
Brand	BKT
Tread pattern	FL 630 Ultra
Valid rim size	AG 24.00 x 22.5 TH2
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	-50
Rim colour	Silver
Rim series	Profiline
Load capacity complete wheel [kg]	6300
Speed complete wheel [km/h]	40
Nettogewicht [kg] (gültig)	203,34
RDA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15715141
LI / SI / PR	172 A8 / 161 D
Load capacity 1 [kg]	6300
Speed 1 [km/h].	40
Load capacity 2 [kg]	4625
Speed 2 [km/h].	65
Maximum air pressure [bar].	4,00

TL/TT	TL
Tyre colour	Black
E-Ready	No
Antistatic	No
ECE regulation number	ECE 106
Section width (mm)	727
Stat. radius (SLR) [mm]	514
Speed Radius Index (SRI)	550
Rolling circumference [mm].	3490
Tread depth (mm)	24,5
Number of lugs	17x2
Tyre capacity 75% [ltr.]	393
Assembly Item no. Rim	• 32012784
Load capacity of rim 1 [kg]	8040
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	6640
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Type of drive	Angetriebene & gezogene Achse
Number of bolt holes	10
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Bolt hole design EUWA	B22 ES 36
Countersinking	Sphere
Spherical countersink [mm].	R18
Rim centering	BC

Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Ventilation holes	No
Single / multi-part	einteilig
Hump	TH2
Cavity Sealed	No
Knurling	without knurling
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201039
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade