

WHEELS

Product group	Wheels
Item number	59940037
Valid wheel size	560 / 60 R 22.5
Brand	BKT
Tread pattern	FL 630 Ultra
Valid rim size	AG 16.00 x 22.5 H2
Rim connection	8/221/275
Bolt hole design	A3
Offset (mm)	+50
Rim colour	Silver
Load capacity complete wheel [kg]	6300
Speed complete wheel [km/h]	40
Nettogewicht [kg] (gültig)	164,65
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15715139
LI / SI / PR	172 A8 / 161 D
Load capacity 1 [kg]	6300
Speed 1 [km/h].	40
Load capacity 2 [kg]	4625
Speed 2 [km/h].	65
Maximum air pressure [bar].	4,00
TL/TT	TL

Tyre colour	Black
E-Ready	No
Antistatic	No
ECE regulation number	ECE 106
Section width (mm)	543
Stat. radius (SLR) [mm]	535
Speed Radius Index (SRI)	600
Rolling circumference [mm].	3760
Tread depth (mm)	28,5
Number of lugs	20x2
Tyre capacity 75% [ltr.]	374
Assembly Item no. Rim	• 33060373
Load capacity of rim 1 [kg]	7250
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	5300
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	40
Type of drive	Towed axle
Number of bolt holes	8
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole design EUWA	B22 ES 36
Countersinking	Sphere
Spherical countersink [mm].	R18
Rim centering	BC
Rim material	steel
RAL	RAL9006

Valve seat	External Valve
Disc thickness [mm]	12.0
Ventilation holes	No
Single / multi-part	einteilig
Hump	H2
Valve protection	VSH
Cavity Sealed	No
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201038
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade