

WHEELS

Product group	Wheels
Item number	59991416
Valid wheel size	320 / 55 - 15
Brand	Carlstar
Tread pattern	Multi Trac C/S
Valid rim size	10 LB x 15
Rim connection	5/94/140
Offset (mm)	-50
Rim colour	Silver
Load capacity complete wheel [kg]	1120
Speed complete wheel [km/h]	50
Nettogewicht [kg] (gültig)	28,15
RDA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No





Technical Informations

Assembly Item no. Tyres	12500689
LI / SI / PR	112 B, 10 PR
Load capacity 1 [kg]	1120
Speed 1 [km/h].	50
Maximum air pressure [bar].	4,15
TL/TT	TL
Tyre colour	Black
E-Ready	No
Antistatic	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



ECE regulation number	ECE 106
Section width (mm)	318
Stat. radius (SLR) [mm]	344
Rolling circumference [mm].	2291
Tread depth (mm)	8,9
Assembly Item no. Rim •	39920407
Maximum speed [km/h].	50
Number of bolt holes	5
hub hole diameter [mm].	94
Bolt hole circle diameter [mm]	140
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Ventilation holes	No
Single / multi-part	einteilig
Hump	kein Hump
Cavity Sealed	No
Verschweißung beidseitig	No
Assembly Item no. Valve	47201038
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade