

## WHEELS

Product group	Wheels
Item number	59991458
Valid wheel size	31 x 15.50 - 15
Brand	BKT
Tread pattern	TR 313
Valid rim size	13 LB x 15 H2
Rim connection	6/161/205
Bolt hole design	A2
Offset (mm)	-55
Rim colour	Silver
Load capacity complete wheel [kg]	1250
Speed complete wheel [km/h]	40
Nettogewicht [kg] (gültig)	42,91
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 15710552
LI / SI / PR	116 B, 8 PR
Load capacity 1 [kg]	1250
Speed 1 [km/h].	50
Maximum air pressure [bar].	3,10
TL/TT	TL
Tyre colour	Black
E-Ready	No

Antistatic	No
ECE regulation number	ECE 106
Section width (mm)	370
Stat. radius (SLR) [mm]	342
Rolling circumference [mm].	2233
Tread depth (mm)	23,5
Number of lugs	19x2
Assembly Item no. Rim	• 32010103
Load capacity of rim 1 [kg]	2000
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Type of drive	Angetriebene & gezogene Achse
Number of bolt holes	6
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Bolt hole diameter [mm]	21.5
Bolt hole design EUWA	B18 ES 32
Countersinking	Sphere
Spherical countersink [mm].	R16
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Ventilation holes	No
Single / multi-part	einteilig
Hump	H2
Cavity Sealed	No

---

Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201039
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade