

WHEELS

Product group	Wheels
Item number	59991522
Valid wheel size	31 x 15.50 R 15
Brand	BKT
Tread pattern	AS 511
Valid rim size	13 x 15
Rim connection	5/94/140
Offset (mm)	-55
Rim colour	Silver
Load capacity complete wheel [kg]	1500
Speed complete wheel [km/h]	50
Nettogewicht [kg] (gültig)	49,27
RDA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15717160
LI / SI / PR	122 B
Load capacity 1 [kg]	1500
Speed 1 [km/h].	50
Maximum air pressure [bar].	2,80
TL/TT	TL
Tyre colour	Black
E-Ready	No
Antistatic	No

ECE regulation number	ECE 106
Section width (mm)	388
Stat. radius (SLR) [mm]	353
Speed Radius Index (SRI)	380
Rolling circumference [mm].	2387
Tread depth (mm)	18,5
Number of lugs	18x2
Assembly Item no. Rim	• 39920423
Load capacity of rim 1 [kg]	3300
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	2500
Speed Rims 2 [km/h]	50
Maximum speed [km/h].	50
Type of drive	Towed axle
Number of bolt holes	5
hub hole diameter [mm].	94
Bolt hole circle diameter [mm]	140
Bolt hole diameter [mm]	15
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Disc thickness [mm]	10
Ventilation holes	No
Single / multi-part	einteilig
Hump	kein Hump
Valve protection	VSH

Cavity Sealed	No
Knurling	without knurling
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47200570
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Rubber valve
Valve designation ETRTO	V2.03.3
Valve length [mm]	43.0
Valve angle [°]	gerade