

## **RIMS**

Product group	Rims
Item number	69122999
Valid rim size	DW 25 x 42
Rim connection	12/814
Bolt hole design	D24
Offset (mm)	+70
Brand	Levypyoera

## **Technical Informations**

Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	225,00
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
Rim colour (manufacturer's designation)	John Deere - yellow
Cavity Sealed	No
Disc thickness [mm]	15
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	НВ

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Number of bolt holes	12
Bolt hole design EUWA	M20
Bolt hole diameter [mm]	24
hub hole diameter [mm].	814
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Geeignet für RDA	No