

TYRES

Product group	Tyres
Item number	71940011
Valid tyre size	600 / 70 R 34
LI / SI / PR	160 D / 157 E
Brand	Trelleborg
Tread pattern	ТМ900НР
type of damage	Dismounted





Notes and features

- The TM 900 High Power was developed specifically for the biggest agricultural machines and high-performance tractors.
- It offers extremely high load capacity.

- Due to its special design, the tyre transmits the vehicle's high torque and enables high traction on all soils.
- It is characterised through extraordinarily high ride comfort and safety.



Technical Informations

Item number	71940011
EAN	4040658099151
Valid tyre size	600 / 70 R 34
LI / SI / PR	160 D / 157 E
Brand	Trelleborg
Tread pattern	TM900HP
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	193,00
Maximum air pressure [bar].	2,40
Section width (mm)	600
Outer diameter of tyre [mm].	1685
Stat. radius (SLR) [mm]	755
Rolling circumference [mm].	5105
Tread depth (mm)	55,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 D	4500	65		2,40	
157 E	4125	70		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.